



THE ABOVE DATA IS STRICTLY RATED; A VARIATION IN ANY OF THE DATA LEADS TO A CONSEQUENT VARIATION IN ALL OTHER DATA.  
SYSTEM DI ROSATI RESERVES THE RIGHT TO MAKE CHANGES TO THE DIMENSIONS AND CHARACTERISTICS DESCRIBED ON THIS  
DATA SHEET WITHOUT PRIOR NOTICE.

## DATA SHEET

		RA400	RA700	RA900
RATED POWER SUPPLY	V	230	230	230
ABSORBED CURRENT	A	1,8	3	4
ABSORBED POWER	W	400	700	900
TYPE POWER		VAC	VAC	VAC
SERVICE	ED%	100	100	100
* WORKING THERMOSTAT AUTOMATIC RESET	°C	55±10%	55±10%	55±10%
* VARIOUS TEMPERATURE ON REQUEST				
** SAFETY THERMOSTAT AUTOMATIC RESET	°C	85±10%	85±10%	85±10%
** SAFETY THERMOSTAT MANUAL RESET ON REQUEST				
*** THERMOSTAT ON/OFF CYCLES	No	100.000	100.000	100.000
*** THE NUMBER OF CYCLES VARY ACCORDING TO THE APPLICATION				
INSULATION CLASS	CLASS	1	1	1
DIELECTRIC STRENGTH	V/SEC	1500/3	1500/3	1500/3
HEATER PROTECTION DEGREE	IP	65	65	65
TANK PRESSURE	BAR	6	6	6
TANK CAPACITY	L	1	1	1
TOTAL HEATER WEIGHT	Kg	2,500	2,500	2,500