



THE ABOVE DATA IS STRICTLY RATED; A VARIATION IN ANY OF THE DATA LEADS TO A CONSEQUENT VARIATION IN ALL OTHER DATA.
SYSTEM DI ROSATI RESERVES THE RIGHT TO MAKE CHANGES TO THE DIMENSIONS AND CHARACTERISTICS DESCRIBED ON THIS
DATA SHEET WITHOUT PRIOR NOTICE.

DIMENSIONS

MODEL	A	B	C	D	E	F	G	H	I
RA1200	314	447,5	70	109	300	GAS 1/2	65	140	112
RA3000	386	519,5	129	125	372	GAS 3/4	93	168.5	140

DATA SHEET

		RA1200	RA3000
RATED POWER SUPPLY	V	230	230
ABSORBED CURRENT	A	5.2	13
ABSORBED POWER	W	1200	3000
TYPE POWER		VAC	VAC
SERVICE	ED%	100	100
MAX ADJUSTABLE TEMPERATURE OF THE WORK THERMOSTAT	°C	80±10%	80±10%
SAFETY THERMOSTAT MANUAL RESET	°C	100±10%	100±10%
* THERMOSTAT ON/OFF CYCLES	No	25.000	25.000
* THE NUMBER OF CYCLES VARY ACCORDING TO THE APPLICATION			
INSULATION CLASS	CLASS	1	1
DIELECTRIC STRENGTH	V/SEC	1500/3	1500/3
HEATER PROTECTION DEGREE	IP	65	65
TANK PRESSURE	BAR	6	6
TANK CAPACITY	L	2	4,5
TOTAL HEATER WEIGHT	Kg	4,200	6,300