



DIMENSIONS

MODEL	A	B	C
RO350	215	143	115
RO700	299	227	160

THE ABOVE DATA IS STRICTLY RATED; A VARIATION IN ANY OF THE DATA LEADS TO A CONSEQUENT VARIATION IN ALL OTHER DATA.

SYSTEM DI ROSATI RESERVES THE RIGHT TO MAKE CHANGES TO THE DIMENSIONS AND CHARACTERISTICS DESCRIBED ON THIS DATA SHEET WITHOUT PRIOR NOTICE.

DATA SHEET

		RO350	RO700
RATED POWER SUPPLY	V	230	230
ABSORBED CURRENT	A	1.60	3.20
ABSORBED POWER	W	350	700
TYPE POWER		VAC	VAC
SERVICE	ED%	100	100
OPERATING TEMPERATURE (FACTORY CALIBRATED)	°C	45±10%	45±10%
MAX OPERATING TEMPERATURE (ADJUSTABLE)	°C	80±10%	80±10%
THERMOSTAT ON-OFF CYCLES	No	25000	25000
INSULATION CLASS	CLASS	1	1
DIELECTRIC STRENGTH	V/SEC	1500/3	1500/3
HEATER PROTECTION DEGREE	IP	65	65
TOTAL HEATER WEIGHT	Kg	2,800	3,800